

View Online at <https://aerobasegroup.com/nsn/5306-00-832-9775>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.889 inches

**Fastener Length:**

2.812 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

1.125 inches

**Head Height:**

0.312 inches

**Width Between Flats:**

0.748 inches

**Grip Diameter:**

Between 0.6234 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

1.812 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.125 inches first hole

**Material:**

Steel

**Material Specification:**

Ms555-fscm 88277 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ps928 fscm 88277 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0