## NSN 5306-00-833-2371

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-833-2371

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.351 inches
Fastener Length:
0.664 inches
Head Style:
Double hexagon
Head Height:
0.187 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.3108 inches and 0.3117 inches
Thread Diameter:
0.312 inches
Grip Length:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 220000 pounds per square inch
<del>-</del>
220000 pounds per square inch
220000 pounds per square inch Hardness Rating:
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:
220000 pounds per square inch  Hardness Rating: 46.0 rockwell c and 50.0 rockwell c  Material:  Steel
220000 pounds per square inch  Hardness Rating: 46.0 rockwell c and 50.0 rockwell c  Material: Steel  Material Specification:
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response
220000 pounds per square inch  Hardness Rating: 46.0 rockwell c and 50.0 rockwell c  Material: Steel  Material Specification: Sps-m-107, fscm 03680 mfr ref single material response Surface Treatment:
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Nas 672 assn standard single treatment response
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Nas 672 assn standard single treatment response  Thread Series Designator:
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Nas 672 assn standard single treatment response  Thread Series Designator:  Unjf
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Nas 672 assn standard single treatment response  Thread Series Designator:  Unjf  Specification Data:
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Nas 672 assn standard single treatment response  Thread Series Designator:  Unjf  Specification Data:  26512-gb511b manufacturers standard
220000 pounds per square inch  Hardness Rating:  46.0 rockwell c and 50.0 rockwell c  Material:  Steel  Material Specification:  Sps-m-107, fscm 03680 mfr ref single material response  Surface Treatment:  Cadmium  Surface Treatment Specification:  Nas 672 assn standard single treatment response  Thread Series Designator:  Unjf  Specification Data:  26512-gb511b manufacturers standard  Shelf Life:

--

## NSN 5306-00-833-2371

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0