

View Online at <https://aerobasegroup.com/nsn/5306-00-834-1367>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.547 inches and 0.597 inches

Fastener Length:

Between 1.182 inches and 1.212 inches

Head Style:

Dished hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.054 inches first hole and 1.094 inches first hole

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1112 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.