NSN 5306-00-835-1714

Machine Bolt - Page 1 of 2

Between 0.730 inches and 0.770 inches

Thread Direction:

Thread Length:

Fastener Length:

Right-hand



View Online at https://aerobasegroup.com/nsn/5306-00-835-1714

| Between 1.678 inches and 1.698 inches |
|---|
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.240 inches and 0.260 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.062 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.928 inches and 0.948 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Nonstandard Thread Pitch Diameter: |
| +0.2405/+0.2470 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hardness Rating: |
| 30.0 rockwell c and 38.0 rockwell c |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel comp 601 |
| Material Specification: |
| Ams 6304 assn standard single material response |
| Surface Treatment: |
| Nickel and cadmium |
| Surface Treatment Specification: |
| Ams 2416 assn standard all treatment responses |
| Thread Series Designator: |
| Unf |
| |

NSN 5306-00-835-1714

Machine Bolt - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0