

View Online at <https://aerobasegroup.com/nsn/5306-00-835-4775>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.218 inches and 1.282 inches

**Fastener Length:**

Between 3.796 inches and 3.828 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.453 inches and 0.485 inches

**Width Between Flats:**

Between 1.240 inches and 1.250 inches

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 2.546 inches and 2.578 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.