## NSN 5306-00-837-2590

Machine Bolt - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.625 inches Fastener Length: Between 1.359 inches and 1.375 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.306 inches and 0.312 inches Width Between Flats: Between 0.308 inches and 0.314 inches **Extended Washer Diameter:** Between 0.457 inches and 0.496 inches **Extended Washer Thickness:** 0.090 inches **Thread Diameter:** 0.312 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 42.0 rockwell c **Minimum Yield Strength:** 150000 pounds per square inch Material: Steel comp 8637 **Material Specification:** Astm a547 assn standard single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a

## NSN 5306-00-837-2590

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

