

View Online at <https://aerobasegroup.com/nsn/5306-00-838-1654>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.469 inches

**Fastener Length:**

Between 0.704 inches and 0.734 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Locking Feature:**

Pellet threads

**Grip Diameter:**

Between 0.311 inches and 0.312 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.240 inches and 0.260 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c fastener and 40.0 rockwell c fastener

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener

**Material Specification:**

Mil-s-5000 military specification 1st material response fastener or mil-s-5626 military specification 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener or mil-s-6098 military specification 4th material response fastener or mil-s-8503 military specification 5th material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1225 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.