

View Online at <https://aerobasegroup.com/nsn/5306-00-839-1632>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.400 inches and 0.490 inches

**Fastener Length:**

Between 1.630 inches and 1.690 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.170 inches

**Width Between Flats:**

Between 0.428 inches and 0.440 inches

**First Diameter From Head:**

Between 0.244 inches and 0.250 inches

**Second Diameter From Head:**

Between 0.204 inches and 0.209 inches

**Third Diameter From Head:**

Between 0.244 inches and 0.250 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.370 inches and 0.380 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.900 inches and 0.930 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 1.200 inches and 1.230 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

34.0 rockwell c and 44.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Stainless steel

**Material Specification:**

Ams 5706 assn standard single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0