NSN 5306-00-839-5533

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-839-5533 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.580 inches and 0.600 inches **Fastener Length:** Between 4.185 inches and 4.205 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.459 inches and 0.469 inches **Extended Washer Thickness:** Between 0.070 inches and 0.090 inches **First Diameter From Head:** Between 0.270 inches and 0.290 inches **Second Diameter From Head:** Between 0.490 inches and 0.495 inches **Third Diameter From Head:** Between 0.240 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 2.235 inches and 2.255 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.325 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 3.585 inches and 3.625 inches **Thread Diameter:** 0.3125 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity:** 3 Material: Steel **Material Specification:** Ams 7477 assn standard single material response

Unf

Thread Series Designator:

NSN 5306-00-839-5533

Externally Relieved Body Bolt - Page 2 of 2



		fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0