## NSN 5306-00-840-0068



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-840-0068 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.657 inches **Fastener Length:** 3.219 inches **Head Style:** Hexagon **Head Height:** Between 0.234 inches and 0.266 inches Width Between Flats: Between 0.615 inches and 0.627 inches **Thread Diameter:** 0.438 inches **Grip Length:** 2.562 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard 6th material response **Surface Treatment:** Cadmium or chromate **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:** 

## NSN 5306-00-840-0068

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.