NSN 5306-00-841-6999

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-841-6999 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 2.812 inches **Head Style:** Dee chamfer **Head Diameter:** 1.000 inches **Head Height:** 0.312 inches **Distance From Centerline To Flat:** 0.375 inches First Diameter From Head: 0.562 inches **Second Diameter From Head:** 0.623 inches **Third Diameter From Head:** 0.535 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.875 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.062 inches **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 27.0 rockwell c and 32.0 rockwell c Minimum Yield Strength: 105000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 3 **Special Features:** 1 locknut furnised; both ends center drilled 0.250 in. By 0.261 in. By 60 deg

Material:

Steel

NSN 5306-00-841-6999

Externally Relieved Body Bolt - Page 2 of 2



Material Specification:
Mil-s-890, alloy 2 military specification single material response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila:

Mil-s-890 spec.

Mil-std (military Standard):

A003b0