

View Online at <https://aerobasegroup.com/nsn/5306-00-842-4232>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.760 inches and 0.800 inches

**Fastener Length:**

Between 2.615 inches and 2.635 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.815 inches and 1.875 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0