

View Online at <https://aerobasegroup.com/nsn/5306-00-842-8198>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 4.203 inches and 4.205 inches

Fastener Length:

Between 4.545 inches and 4.565 inches

Head Style:

Dee

Head Diameter:

Between 0.820 inches and 0.860 inches

Head Height:

Between 0.115 inches and 0.135 inches

Distance From Centerline To Flat:

Between 0.355 inches and 0.375 inches

Shoulder Diameter:

Between 0.538 inches and 0.539 inches

Shoulder Length:

Between 0.870 inches and 0.930 inches

Shank Unthreaded Hole Diameter:

0.065 inches first hole and 0.072 inches first hole

Concentric Hole Depth:

Between 4.050 inches and 4.090 inches

Concentric Hole Diameter:

Between 0.329 inches and 0.349 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.300 inches first hole and 4.330 inches first hole

Askewed Head Angle:

Between 43.0 degrees and 47.0 degrees

Material:

Nickel alloy

Material Specification:

Ams 5667 assn standard single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Ams 2406 assn standard single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0