NSN 5306-00-843-1791

Machine Bolt - Page 1 of 2

Between 0.886 inches and 0.926 inches

Between 1.178 inches and 1.198 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

1a



View Online at https://aerobasegroup.com/nsn/5306-00-843-1791

| Head Style: |
|---|
| Double hexagon w/hole |
| Head Height: |
| Between 0.365 inches and 0.385 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Extended Washer Diameter: |
| Between 0.490 inches and 0.510 inches |
| Extended Washer Thickness: |
| Between 0.070 inches and 0.080 inches |
| Hole Diameter: |
| 0.062 inches |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.252 inches and 0.312 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hardness Rating: |
| 30.0 rockwell c and 38.0 rockwell c |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Material: |
| Steel comp 601 |
| Material Specification: |
| |
| Ams 6304 assn standard single material response |
| Ams 6304 assn standard single material response Surface Treatment: |
| |
| Surface Treatment: |

NSN 5306-00-843-1791 Machine Bolt - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

Fiig:

No

A003b0