Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-844-7512

| Inre | ad Class: |
|-------------------|--|
| 3a | |
| Thre | ad Direction: |
| Righ | t-hand |
| Thre | ad Length: |
| 0.91 |) inches |
| Fast | ener Length: |
| 3.73 | 5 inches |
| Head | d Style: |
| Hexa | agon |
| Head | d Height: |
| 0.33 |) inches |
| Widt | h Between Flats: |
| 0.61 | 9 inches |
| First | Diameter From Head: |
| 0.43 | 4 inches |
| Seco | ond Diameter From Head: |
| 0.38 | 9 inches |
| Dista | ance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.28 |) inches |
| Dista | ance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 2.82 | 5 inches |
| Thre | ad Diameter: |
| 0.43 [.] | 7 inches |
| Thre | ady Qty Per Inch (tpi): |
| 14 | |
| Hard | Iness Rating: |
| 37.9 | rockwell c |
| Exte | rnally Relieved Body Diameter Quantity: |
| 2 | |
| Mate | erial: |
| Stee | l comp 1010 |
| Mate | rial Specification: |
| Qq-s | -633 federal specification single material response |
| Thre | ad Series Designator: |
| Unc | |
| Shel | f Life: |
| N/a | |
| Unit | Of Measure: |
| | |
| Dem | ilitarization: |

NSN 5306-00-844-7512

Externally Relieved Body Bolt - Page 2 of 2

Fiig: A003b0

