

View Online at <https://aerobasegroup.com/nsn/5306-00-849-1624>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.313 inches and 0.363 inches

Fastener Length:

Between 1.198 inches and 1.228 inches

Head Style:

Hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.045 inches first hole and 1.065 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas673 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0