NSN 5306-00-849-8391



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-849-8391 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.400 inches **Fastener Length:** Between 1.965 inches and 1.985 inches **Head Style:** Hexagon **Head Height:** Between 0.146 inches and 0.166 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Shank Unthreaded Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.494 inches and 1.554 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 1.860 inches first hole and 1.870 inches first hole **Surface Finish:** 63.0 microinches grip Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-00-849-8391 Machine Bolt - Page 2 of 2



| | | eas | |
|--|--|-----|--|

Demilitarization:

No

Fiig:

A003b0