NSN 5306-00-849-9565

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-849-9565
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.812 inches
Fastener Length:
Between 2.812 inches and 2.827 inches
Head Style:
Double hexagon extended washer
Head Height:
Between 0.365 inches and 0.385 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.490 inches and 0.510 inches
Extended Washer Thickness:
Between 0.070 inches and 0.080 inches
First Diameter From Head:
Between 0.307 inches and 0.312 inches
Second Diameter From Head:
Between 0.245 inches and 0.250 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.245 inches and 0.260 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 1.940 inches and 2.000 inches
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
25.0 rockwell c and 30.0 rockwell c
Externally Relieved Body Diameter Quantity:
2
Material:
Steel comp 8740
Material Specification:
Ams 6322 assn standard single material response
Surface Treatment:
Cadmium
Thread Series Designator:

Unf

NSN 5306-00-849-9565

Externally Relieved Body Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0