## NSN 5306-00-850-6115

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-850-6115 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.770 inches **Fastener Length:** 3.000 inches **Head Style:** Hexagon **Head Height:** 0.468 inches Width Between Flats: 1.125 inches **First Diameter From Head:** Between 0.745 inches and 0.755 inches **Second Diameter From Head:** Between 0.615 inches and 0.625 inches **Third Diameter From Head:** Between 0.745 inches and 0.755 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.235 inches and 0.265 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.515 inches and 1.545 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.810 inches **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 10 **Externally Relieved Body Diameter Quantity: Special Features:** 0.430 in. Lg unthd porition at end of bolt and 0.180 in. Lg by 30.0 degrees chamfered end Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** 

Unc

**Thread Series Designator:** 

Qq-p-35 federal specification single treatment response

## NSN 5306-00-850-6115

Externally Relieved Body Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0