

View Online at <https://aerobasegroup.com/nsn/5306-00-850-7604>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.295 inches and 0.335 inches

Fastener Length:

Between 0.775 inches and 0.795 inches

Head Style:

Hexagon

Head Height:

Between 0.080 inches and 0.100 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Shoulder Diameter:

0.371 inches first shoulder and 0.372 inches first shoulder

Shoulder Length:

0.130 inches first shoulder and 0.134 inches first shoulder

Shank Unthreaded Hole Diameter:

0.065 inches first hole and 0.072 inches first hole

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.650 inches first hole and 0.670 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Ams 2406 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0