

View Online at <https://aerobasegroup.com/nsn/5306-00-852-9240>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.188 inches

Fastener Length:

1.875 inches

Head Style:

Hexagon extended washer

Head Height:

0.281 inches

Width Between Flats:

Between 0.490 inches and 0.502 inches

Extended Washer Diameter:

0.875 inches

Extended Washer Thickness:

0.063 inches

Shoulder Diameter:

0.5530 inches first shoulder and 0.5550 inches first shoulder

Shoulder Length:

0.500 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.719 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 cond f-4 military specification single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.