

View Online at <https://aerobasegroup.com/nsn/5306-00-853-1689>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.289 inches and 1.339 inches

Fastener Length:

Between 5.299 inches and 5.329 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.780 inches and 0.840 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Extended Washer Diameter:

Between 1.415 inches and 1.425 inches

Extended Washer Thickness:

Between 0.120 inches and 0.180 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 3.990 inches and 4.010 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 53.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 ty2 cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.