## NSN 5306-00-853-1689

Shear Bolt - Page 1 of 2



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.289 inches and 1.339 inches
Fastener Length:
Between 5.299 inches and 5.329 inches
Head Style:
Double hexagon extended washer
Head Height:
Between 0.780 inches and 0.840 inches
Width Between Flats:
Between 0.928 inches and 0.940 inches
Extended Washer Diameter:
Between 1.415 inches and 1.425 inches
Extended Washer Thickness:
Between 0.120 inches and 0.180 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Thread Diameter:
0.750 inches
0.750 inches  Grip Length:
Grip Length:
Grip Length: Between 3.990 inches and 4.010 inches
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch  Hardness Rating:
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 53.0 rockwell c
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 53.0 rockwell c  Material:
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 53.0 rockwell c  Material:  Steel comp h11
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 53.0 rockwell c  Material:  Steel comp h11  Material Specification:
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 53.0 rockwell c  Material:  Steel comp h11  Material Specification:  Ams 6485 assn standard single material response or ams6487 assn standard single material response
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi): 260000 pounds per square inch  Hardness Rating: 51.0 rockwell c and 53.0 rockwell c  Material: Steel comp h11  Material Specification:  Ams 6485 assn standard single material response or ams6487 assn standard single material response  Surface Treatment:
Grip Length: Between 3.990 inches and 4.010 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 53.0 rockwell c Material: Steel comp h11 Material Specification: Ams 6485 assn standard single material response or ams6487 assn standard single material response Surface Treatment: Cadmium and chromate
Grip Length:  Between 3.990 inches and 4.010 inches  Thready Qty Per Inch (tpi):  16  Min. Tensile Strength (psi):  260000 pounds per square inch  Hardness Rating:  51.0 rockwell c and 53.0 rockwell c  Material:  Steel comp h11  Material Specification:  Ams 6485 assn standard single material response or ams6487 assn standard single material response  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:
Grip Length: Between 3.990 inches and 4.010 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 53.0 rockwell c Material: Steel comp h11 Material Specification: Ams 6485 assn standard single material response or ams6487 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Mil-c-8837 ty2 cl2 military specification single treatment response

N/a

## NSN 5306-00-853-1689

Shear Bolt - Page 2 of 2



Unit Of Meası
---------------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.