## **NSN 5306-00-853-2904** Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-853-2904
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
1.094 inches
Head Style:
Hexagon
Head Height:
0.219 inches
Width Between Flats:
0.625 inches
Grip Diameter:
0.4367 inches
Single Shear Strength:
14300 pounds per square inch
Thread Diameter:
0.438 inches
Grip Length:
0.625 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th materia
response or mil-s-8695 military specification 6th material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Thread Series Designator:
Unf

N/a

Shelf Life:

## NSN 5306-00-853-2904

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.