

View Online at <https://aerobasegroup.com/nsn/5306-00-855-2012>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.625 inches

Fastener Length:

3.625 inches

Head Style:

Double hexagon extended washer

Head Height:

0.300 inches

Width Between Flats:

Between 0.305 inches and 0.313 inches

Extended Washer Diameter:

0.438 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

First Diameter From Head:

Between 0.244 inches and 0.249 inches

Second Diameter From Head:

Between 0.190 inches and 0.195 inches

Third Diameter From Head:

Between 0.2489 inches and 0.2495 inches

Fourth Diameter From Head:

Between 0.190 inches and 0.195 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.200 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.400 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.600 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

3.000 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Externally Relieved Body Diameter Quantity:

4

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0