

View Online at <https://aerobasegroup.com/nsn/5306-00-855-2012>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.625 inches

**Fastener Length:**

3.625 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.300 inches

**Width Between Flats:**

Between 0.305 inches and 0.313 inches

**Extended Washer Diameter:**

0.438 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**First Diameter From Head:**

Between 0.244 inches and 0.249 inches

**Second Diameter From Head:**

Between 0.190 inches and 0.195 inches

**Third Diameter From Head:**

Between 0.2489 inches and 0.2495 inches

**Fourth Diameter From Head:**

Between 0.190 inches and 0.195 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.200 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.400 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.600 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

3.000 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0