Internally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-857-2498

Interact Class, a a Thread Direction: Right-hand Thread Length: 1.240 inches 1.240	Thread Class:
Furead Direction:Righ-hand1-240 inches1-240 inches8-steer Length:0.100 inchesHead Siyle:Head Siyle:Head Heigh:0.380 inchesWith Between Flats:0.380 inchesWith Between Flats:1.080 inchesShoulder Diameter:Between 0.747 inches and 0.749 inchesShoulder Diameter:0.590 inchesShoulder Diameter:0.590 inchesBetween 6.070 inches and 6.130 inchesConcentric Hole Depth:0.590 inchesChread Diameter:0.590 inchesChread Diameter:0.500 inchesChread Diameter:	
Right-hand         Thread Length:         1.240 Inches         Fastener Length:         9.190 Inches         Head Style:         Head Style:         Head Style:         0.380 Inches         With Herven Flats:         0.380 Inches         Schulder Diameter:         1.050 Inches         Schulder Diameter:         0.495 Inches         Concentric Hole Depth:         7.950 Inches         Concentric Hole Dameter:         0.500 Inches         Thread Diameter:         0.500 Inches         Thread Seine Institution         Stell         Stell         Stell         Stell         Stell         Stell Enstitution         Concentric Hole Unithreaded         Thread Seines Designator:         Concentric Hole Unithreaded         Thread Seines Designator:         Unit Measure: <tr< th=""><th></th></tr<>	
Thread Length:1.240 inchesFactor Length:9.190 inchesHead Style:Head Style:Head Style:1.640 inchesWith Between Flats:1.060 inchesShoulder Diameter:1.060 inchesShoulder Length:7.950 inchesGoncentric Hole Depth:8.000 inchesConcentric Hole Depth:0.625 inchesThread Diameter:0.626 inchesBetween 0.707 inches and 0.749 inchesBetween 0.707 inches and 0.749 inchesConcentric Hole Depth:8.000 inchesConcentric Hole Diameter:0.625 inchesChread Yang Per Inch (tpl):18Material:Stoll Genetic:CardiniSturder Teatment:CardiniCardiniSturder Stell Designator:Interial:NaChread Stells:NaStell Life:NaStell Life:NaStell Life:NaStell Life:NaStell Life:NaStell Life:NaNaStell Life:NaStell Life:NaStell Life:NaStell Life:NaStell Life:NaStell Life:NaStell Life:Stell Life:Stell Life:Stell Life:Stell Life:Stell	
1240 inches         Fastener Length:         9.190 inches         Head Style:         Head Asyle:         Head Height:         0.380 inches         With Between Flats:         1.060 inches         Shoulder Diameter:         Between 0.747 inches and 0.749 inches         Shoulder Length:         2.950 inches         Concentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Diameter:         0.500 inches         Thread Quy Per Inch (spl):         18         Material:         Stel         Surface Treatment:         Cadmim         Stel Instrict Hole unthreaded         Thread Series Designator:         Info         Shelf Life:         Na         Shelf Life:         Na         Shelf Life:         Na         Dirt of Measure:         Info         Shelf Life:         Na         Shelf Life:         Na         Shelf Life:         Na	
Fastener Length:         9.190 inches         Hexad Style:         Hexad apon         Hexad Height:         0.380 inches         With Between Flats:         1.060 inches         Shoulder Diameter:         Between 0.747 inches and 0.749 inches         Shoulder Length:         7.950 inches         Occentric Hole Depth:         7.950 inches         Between 6.070 inches and 6.130 inches         Concentric Hole Depth:         0.500 inches         Thread Diameter:         0.500 inches         17head Diameter:         0.500 inches         Thread Diameter:         0.625 inches         Thread Diameter:         0.625 inches         Stell         Stell         Stell         Gardinim         Stell         Stell         Stell         Stell         Stell         Stell         Stell         Stell         Stell (Stell (	
9.190 inches Head Style: Head Style: Head Paignet Head Heighet: O 3.80 inches Head Heighet: O 3.80 inches Wicht Between Flats: I 1.600 inches Studter Diameter: O 4.000 inches and 0.749 inches Stouder Lengthet O 5.000 inches and 0.749 inches O 5.000 inches and 0.130 inches Concentric Hole Depth: O 5.000 inches Concentric Hole Depth: O 5.000 inches Concentric Hole Diameter: O 5.000 inches Concentric Hole	
Head Style:         Hexagon         Head Height:         0.300 Inches         Width Between Flats:         1.060 Inches         Shoulder Diameter:         Between 0.747 Inches and 0.749 Inches         Shoulder Length:         7.950 Inches         Concentric Hole Depth:         Between 6.070 Inches and 6.130 Inches         Concentric Hole Diameter:         0.500 Inches         Thread Diameter:         0.550 Inches         Thread Diameter:         0.550 Inches         Thread Diameter:         0.550 Inches         Thread Diameter:         0.652 Inches         Thread Y by Per Inch (pj):         18         Material:         Steel         Steel         Concentric Hole unthreaded         Thread Series Designator:         Concentric Incle unthreaded         Thread Series Designator:         Inf         Stelf Life:         Na         Inf         Stelf Life:         Na         Stelf Life:         Na         Stelf Life:      Na         Stelf Life:	
Heagon         Head Height:         0.380 Inches         With Between Flats:         1.060 Inches         Shoulder Diameter:         Between 0.747 Inches and 0.749 Inches         Shoulder Length:         7.950 Inches         Concentric Hole Depth:         Between 6.070 Inches and 6.130 Inches         Concentric Hole Deptn:         0.625 Inches         Thread Diameter:         0.625 Inches         Thread Series         Stel         Stel         Stel         Stel         Style Designator:         Concentric hele unthreaded         Thread Series Designator:         Inf         Na         Stel Itic:         Na         Control for Measure:         Inf         Stel Itic:         Na         Stel Itic:         Na         Stel Itic:         <	
Head Height:         0.380 inches         Width Between Flats:         1.080 inches         Shoulder Diameter:         Between 0.747 inches and 0.749 inches         Shoulder Length:         7.950 inches         Concentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Diameter:         0.625 inches         Thread Diameter:         0.625 inches         Stel         Stel         Stel         Stel         Concentric hole unthreaded         Thread Series Designator:         Uri         Na         Na     <	
0.380 inches         Width Between Flats:         1.060 inches         Shoulder Dameter:         Between 0.747 inches and 0.749 inches         Shoulder Length:         7.950 inches         Ocnoentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Dameter:         0.500 inches         Thread Diameter:         0.500 inches         Thread Diameter:         0.625 inches         Thread Diameter:         0.625 inches         Thread Pathent (tpi):         18         Material:         Stele         Surface Treatment:         Concentric hole unthreaded         Thread Series Designator:         Inf         Material:         Na         Material:         Concentric hole unthreaded         Thread Series Designator:         Inf         Material:         Na         Hote:         Na         Thread Series Designator:         Inf         Serie         Stele         Inf (Inf)         Series Designator:         Inf	
With Between Flats:         1.060 inches         Shoulder Diameter:         Between 0.747 inches and 0.749 inches         Shoulder Length:         7.950 inches         Concentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Diameter:         0.500 inches         Thread Diameter:         0.625 inches         Thread Valve Per Inch (tpi):         18         Material:         Steel         Surface Treatment:         Cancentric Hole unthreaded         Thread Series Designator:         Infered Series Designator:         Via         Materia:         Na         Stel         Strele         Burface Treatment:         Concentric Hole unthreaded         Thread Series Designator:         Infere         Na         Strele         Strele         Directific Hole         Inference         Strele         Strele         Strele         Strele         Strele         Strele         Strele         Strele	
1.080 inches         Shoulder Diameter:         Between 0.747 inches and 0.749 inches         Shoulder Length:         7.950 inches         Concentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Diameter:         0.500 inches         Thread Diameter:         0.625 inches         Thread Qty Per Inch (tpi):         18         Material:         Stel         Concentric hole unthreaded         Thread Series Designator:         Information:         Na         Unit of Measure:         Information:         Na         Dut Of Measure:         Information:         Na         Stel         Stel         Stell         Stell         Difference         Benetister         Stell	
Shoulder Diameter:         Between 0.747 inches and 0.749 inches         Shoulder Length:         7.950 inches         Concentric Hole Depth:         Between 0.070 inches and 0.130 inches         Concentric Hole Diameter:         0.050 inches         Thread Diameter:         0.625 inches         Thread Valler Per Inch (tpi):         18         Material:         Stel         Stel         Stel         Oncentric hole unthreaded         Thread Series Designator:         Uni         Na         Unif         Shall         Na         Intread Series Designator:         Unif         Na         Striac         Thread Series Designator:         Na         Striac         Intread Series Designator:         Na         Striac         Striac <th></th>	
Between 0.747 inches and 0.749 inches         Shoulder Length:         7.950 inches         Concentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Diameter:         0.500 inches         Thread Diameter:         0.625 inches         Thready Qty Per Inch (tpi):         18         Material:         Steel         Stread Nament:         Concentric Hole untereaded         Thread Series Designator:         Concentric Hole untereaded         Thread Series Designator:         Na         Na         Sheft Life:         Na         Find Measure:         Thread Series Designator:         Intre Series Designator:         Na         Sheft Life:         Na         Find Measure:         Thread Series Designator:         Na         Sheft Life:         Na         Sheft Life:         Na         Sheft Life:         Sheft Life:         Sheft Life:         Sheft Life:         Sheft Life:         Sheft Life:         Sheft	
Shoulder Length:7.950 inchesConcentric Hole Depth:Between 6.070 inches and 6.130 inchesConcentric Hole Diameter:0.500 inchesThread Diameter:0.625 inchesThready Qty Per Inch (tpi):18Material:SteelSurface Treatment:Concentric hole unthreadedThread Series Designator:UnfShelf Life:NaDin Concentric hole unthreadedThread Series Designator:UnfShelf Life:NaFine:NaFine:Fine:NaFine:NaFine:NaFine:NaFine:NaFine:NaFine:Fine:NaFine:F	
7.950 inches         Concentric Hole Depth:         Between 6.070 inches and 6.130 inches         Concentric Hole Diameter:         0.500 inches         Thread Diameter:         0.625 inches         Thready Qty Per Inch (tpi):         18         Material:         Steel         Surface Treatment:         Cancentric hole unthreaded         Thread Series Designator:         Unf         Shelf Life:         Na         Ini of Measure:         Ini of Measure:         Ini of Measure:         Ini of Measure:         No         Fig:	
Concentric Hole Depth:Between 6.070 inches and 6.130 inchesConcentric Hole Diameter:0.500 inchesThread Diameter:0.625 inchesThready Qty Per Inch (tpi):18Mareial:SteelSteelStred Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:NaUnit Of Measure:-Denilitarization:NoFig:	
Between 6.070 inches and 6.130 inches         Concentric Hole Diameter:         0.500 inches         Thread Diameter:         0.625 inches         Thready Qty Per Inch (tpi):         18         Material:         Steel         Steel         Sterlow         Gardminn         Concentric hole unthreaded         Thread Series Designator:         Unf         Shelf Life:         N/a         Unit Of Measure:         -         Pomilitarization:         No         Fig:	
Concentric Hole Diameter:0.500 inchesThread Diameter:0.625 inchesThready Qty Per Inch (tpi):18Material:SteelSurface Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:NaDing Masure:TPamilitarization:FFig:	
0.500 inchesThread Diameter:0.625 inchesThready Qty Per Inch (tpi):18Material:SteelSurface Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:N/aDing Masure:TPomilitarization:NoFig:	
Thread Diameter:0.625 inchesThready Qty Per Inch (tpi):18Material:SteelSurface Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:N/aInt of Measure:Demiltarization:NoFig:	
0.625 inches Thready Qty Per Inch (tpi): 18 Material: Steel Strace Treatment: Cadmium Style Designator: Concentric hole unthreaded Thread Series Designator: Unf Shelf Life: N/a Via Fine: Fig:	
Thready Qty Per Inch (tpi):18Material:SteelSurface Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:N/aUnit Of Measure:Demiltarization:NoFig:	
18         Material:         Steel         Surface Treatment:         Cadmium         Style Designator:         Concentric hole unthreaded         Thread Series Designator:         Unf         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	
Material:SteelSurface Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	
SteelSurface Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Surface Treatment:CadmiumStyle Designator:Concentric hole unthreadedThread Series Designator:UnfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Cadmium         Style Designator:         Concentric hole unthreaded         Thread Series Designator:         Unf         Shelf Life:         N/a         Unt Of Measure:            Demilitarization:         No         Fig:	
Style Designator:   Concentric hole unthreaded   Thread Series Designator:   Unf   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	
Concentric hole unthreaded Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig:	
Thread Series Designator:   Unf   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	
Unf Shelf Life: N/a Unit Of Measure:  Demilitarization: No	
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	
N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	
Unit Of Measure:  Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A003b0	Fiig:
	A003b0