

View Online at <https://aerobasegroup.com/nsn/5306-00-860-3956>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.232 inches and 1.388 inches

Fastener Length:

2.793 inches

Head Style:

Flat chamfer

Head Diameter:

1.484 inches

Head Height:

Between 0.245 inches and 0.255 inches

First Diameter From Head:

Between 1.020 inches and 1.030 inches

Second Diameter From Head:

Between 0.741 inches and 0.747 inches

Third Diameter From Head:

Between 0.691 inches and 0.701 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.338 inches and 0.348 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.502 inches and 0.506 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.752 inches and 0.756 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.750 inches

Width Across Flats:

0.568 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0