

View Online at <https://aerobasegroup.com/nsn/5306-00-862-3987>

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

1.220 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 0.615 inches and 0.635 inches

Head Height:

Between 0.240 inches and 0.260 inches

Width Between Flats:

Between 0.490 inches and 0.510 inches

First Diameter From Head:

Between 0.309 inches and 0.312 inches

Second Diameter From Head:

Between 0.235 inches and 0.245 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.260 inches and 0.280 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.330 inches and 0.370 inches

Thread Diameter:

0.312 inches

Nonstandard Thread Pitch Diameter:

+0.2797/+0.2824 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Externally Relieved Body Diameter Quantity:

2

Special Features:

Thd end chamfered 30.0 degrees 0.158 in. Lg by 0.130 in. Dia

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0