

View Online at <https://aerobasegroup.com/nsn/5306-00-867-7887>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.128 inches and 0.151 inches

**Fastener Length:**

Between 0.440 inches and 0.460 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**First Diameter From Head:**

Between 0.189 inches and 0.190 inches

**Second Diameter From Head:**

Between 0.150 inches and 0.155 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.255 inches and 0.275 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.309 inches and 0.322 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

24.0 rockwell c and 36.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5735 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0