NSN 5306-00-869-1983

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-869-1983 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.630 inches **Fastener Length:** Between 3.580 inches and 3.600 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.090 inches **First Diameter From Head:** Between 0.311 inches and 0.313 inches **Second Diameter From Head:** Between 0.250 inches and 0.260 inches **Third Diameter From Head:** Between 0.311 inches and 0.313 inches **Fourth Diameter From Head:** Between 0.250 inches and 0.260 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.010 inches and 1.030 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 2.120 inches and 2.140 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 2.730 inches and 2.750 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Between 2.930 inches and 2.950 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity:**

4

Material:

Nickel alloy

NSN 5306-00-869-1983

Externally Relieved Body Bolt - Page 2 of 2



	Materia	al Sp	ecific	ation:
--	---------	-------	--------	--------

Ams 5708 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0