Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-870-3007

Thread Direct'	
Thread Direction	on:
Right-hand	
Thread Length	:
0.750 inches	
Fastener Leng	
	inches and 4.010 inches
Head Style:	
Hexagon	
Head Height:	
Between 0.146	inches and 0.166 inches
Width Between	ı Flats:
Between 0.430	inches and 0.439 inches
First Diameter	From Head:
	inches and 0.249 inches
Second Diame	ter From Head:
Between 0.190	inches and 0.195 inches
Third Diameter	· From Head:
Between 0.249	inches and 0.250 inches
Fourth Diameter	er From Head:
Between 0.190	inches and 0.195 inches
Distance From	Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.180	inches and 0.220 inches
Distance From	Largest Bearing Surface Of Head To End Of Second Diameter:
Between 1.735	inches and 1.775 inches
Distance From	Largest Bearing Surface Of Head To End Of Third Diameter:
Between 2.050	inches and 2.090 inches
Distance From	Largest Bearing Surface Of Head To End Of Fourth Diameter:
Between 3.200	inches and 3.260 inches
Thread Diamet	er:
0.250 inches	
Nonstandard T	hread Pitch Diameter:
+0.2212/+0.223	8 inches
Thready Qty Po	er Inch (tpi):
28	
Hardness Ratii	ng:
36.0 rockwell c	and 41.0 rockwell c
Externally Reli	eved Body Diameter Quantity:
4	
Material:	
Stainless steel	
Thread Series	Designator:
Unjf	

## NSN 5306-00-870-3007

Externally Relieved Body Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

