

View Online at <https://aerobasegroup.com/nsn/5306-00-870-3015>

**Thread Class:**

1a

**Thread Direction:**

Right-hand

**Thread Length:**

0.660 inches

**Fastener Length:**

Between 3.640 inches and 3.660 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.146 inches and 0.166 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**First Diameter From Head:**

Between 0.244 inches and 0.249 inches

**Second Diameter From Head:**

Between 0.190 inches and 0.195 inches

**Third Diameter From Head:**

Between 0.249 inches and 0.250 inches

**Fourth Diameter From Head:**

Between 0.190 inches and 0.195 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.190 inches and 0.210 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.475 inches and 1.515 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 1.715 inches and 1.755 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

Between 2.940 inches and 3.000 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Stainless steel

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0