

View Online at <https://aerobasegroup.com/nsn/5306-00-870-8875>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.430 inches and 0.511 inches

**Fastener Length:**

Between 3.960 inches and 3.980 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.320 inches and 0.340 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Shank Unthreaded Hole Diameter:**

0.060 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 3.449 inches and 3.550 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.860 inches first hole

**Product Name:**

Navy special project

**Special Features:**

Tapped hole in head along longitudinal axis 0.190-24 nc-2b by 0.200 in. Deep

**Material:**

Stainless steel

**Material Specification:**

Ams 5625 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0