

View Online at <https://aerobasegroup.com/nsn/5306-00-870-8875>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.430 inches and 0.511 inches

Fastener Length:

Between 3.960 inches and 3.980 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Shank Unthreaded Hole Diameter:

0.060 inches first hole and 0.080 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 3.449 inches and 3.550 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.860 inches first hole

Product Name:

Navy special project

Special Features:

Tapped hole in head along longitudinal axis 0.190-24 nc-2b by 0.200 in. Deep

Material:

Stainless steel

Material Specification:

Ams 5625 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0