

View Online at <https://aerobasegroup.com/nsn/5306-00-877-6986>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.941 inches

Fastener Length:

Between 1.176 inches and 1.206 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.547 inches and 0.567 inches

Width Between Flats:

Between 0.619 inches and 0.628 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.123 inches and 0.143 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Iron alloy 660 or steel comp 302

Surface Treatment:

Passivate or silver

Surface Treatment Specification:

Mil-s-5002 military specification 1st treatment response or qq-s-365 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.