

View Online at <https://aerobasegroup.com/nsn/5306-00-878-0338>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.366 inches and 0.406 inches

Eye Inside Diameter:

Between 0.313 inches and 0.323 inches

Shoulder Thickness:

Between 0.084 inches and 0.104 inches

Shank Length:

Between 0.834 inches and 0.854 inches

Eye Stock Thickness:

Between 0.170 inches and 0.180 inches

Shoulder Diameter:

Between 0.660 inches and 0.720 inches

Overall Length:

Between 1.788 inches and 1.888 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Center Of Eye To Shank End:

1.500 inches

Eye Outside Width:

Between 0.660 inches and 0.720 inches

Special Features:

Rip diameter 0.498 in. Min, 0.502 in. Max

Material:

Steel

Material Specification:

Ams 5355 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

204-947-002, fscm 97499 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0