

View Online at <https://aerobasegroup.com/nsn/5306-00-878-9475>

Thread Direction:

Right-hand

Thread Length:

Between 0.443 inches and 0.446 inches

Fastener Length:

Between 0.740 inches and 0.760 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.285 inches and 0.305 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

Between 0.040 inches and 0.060 inches

First Diameter From Head:

0.189 inches

Second Diameter From Head:

Between 0.137 inches and 0.141 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.250 inches and 0.260 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.297 inches and 0.314 inches

Thread Diameter:

0.190 inches

Nonstandard Thread Pitch Diameter:

+0.1644/+0.1667 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

24.0 rockwell c and 37.0 rockwell c

Externally Relieved Body Diameter Quantity:

2

Material:

Iron alloy 660

Material Specification:

Ams 5735 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0