

View Online at <https://aerobasegroup.com/nsn/5306-00-879-2127>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.380 inches and 0.460 inches

Fastener Length:

Between 2.230 inches and 2.270 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.550 inches and 0.570 inches

Head Height:

Between 0.150 inches and 0.170 inches

Hole Diameter:

0.055 inches

First Diameter From Head:

Between 0.338 inches and 0.348 inches

Second Diameter From Head:

Between 0.280 inches and 0.300 inches

Third Diameter From Head:

Between 0.338 inches and 0.340 inches

Fourth Diameter From Head:

Between 0.230 inches and 0.234 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.120 inches and 0.160 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.610 inches and 1.630 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 1.710 inches and 1.730 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 1.810 inches and 1.850 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

Between 0.187 inches and 0.191 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Round longitudinal hole

Material:

Steel comp 302

Material Specification:

Ams 5637 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0