## NSN 5306-00-879-5954

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-879-5954

## **Thread Direction: Right-hand Thread Length:** Between 0.884 inches and 0.932 inches Fastener Length: Between 1.552 inches and 1.572 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches Hole Diameter: 0.062 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.620 inches and 0.688 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head **Nonstandard Thread Pitch Diameter:** +0.2797/+0.2824 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel comp 601 **Material Specification:**

Ams 6304 assn standard single material response

## NSN 5306-00-879-5954

Machine Bolt - Page 2 of 2



Surface Treatment: Nickel and cadmium Surface Treatment Specification: Ams 2416 assn standard all treatment responses Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A003b0