

View Online at <https://aerobasegroup.com/nsn/5306-00-880-2602>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.670 inches and 0.720 inches

Fastener Length:

Between 2.680 inches and 2.700 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 1.490 inches and 1.510 inches

Head Height:

Between 0.115 inches and 0.135 inches

Width Between Flats:

Between 1.280 inches and 1.290 inches

Shank Unthreaded Hole Diameter:

0.136 inches first hole

First Diameter From Head:

Between 0.7490 inches and 0.7493 inches

Second Diameter From Head:

Between 0.530 inches and 0.550 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 1.890 inches and 1.910 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.980 inches

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

18

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.490 inches first hole and 2.510 inches first hole

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, cl 2 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.