

View Online at <https://aerobasegroup.com/nsn/5306-00-880-6677>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.340 inches and 0.370 inches

Fastener Length:

Between 0.725 inches and 0.750 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.250 inches and 0.270 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

Between 0.040 inches and 0.050 inches

First Diameter From Head:

Between 0.161 inches and 0.171 inches

Second Diameter From Head:

Between 0.207 inches and 0.208 inches

Third Diameter From Head:

Between 0.161 inches and 0.171 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.052 inches and 0.062 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.270 inches and 0.290 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 0.340 inches and 0.380 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

3

Material:

Iron alloy 660

Material Specification:

Ams 5735 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0