## NSN 5306-00-880-6677

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-880-6677 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.340 inches and 0.370 inches **Fastener Length:** Between 0.725 inches and 0.750 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **First Diameter From Head:** Between 0.161 inches and 0.171 inches **Second Diameter From Head:** Between 0.207 inches and 0.208 inches **Third Diameter From Head:** Between 0.161 inches and 0.171 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.052 inches and 0.062 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.270 inches and 0.290 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Between 0.340 inches and 0.380 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** 

Unf

Ams 5735 assn standard single material response

**Thread Series Designator:** 

## NSN 5306-00-880-6677

Externally Relieved Body Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0