

View Online at <https://aerobasegroup.com/nsn/5306-00-881-0117>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.615 inches and 0.695 inches

**Fastener Length:**

Between 0.740 inches and 0.760 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**Hole Diameter:**

0.046 inches

**Grip Length:**

Between 0.065 inches and 0.125 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Nonstandard Thread Pitch Diameter:**

+0.1664/+0.1667 inches

**Hardness Rating:**

42.0 rockwell c and 46.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Surface Finish:**

63.0 microinches grip

**Special Features:**

Min0rdia0fthd0.1487in.Max

**Material:**

Steel comp 601

**Material Specification:**

Ams 630 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0