Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-881-3220

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.390 inches |
| Fastener Length: |
| 0.765 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.140 inches and 0.172 inches |
| Width Between Flats: |
| Between 0.428 inches and 0.440 inches |
| Hole Diameter: |
| 0.062 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.375 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| |
| Hardness Rating: |
| Hardness Rating: 36.0 rockwell c and 40.0 rockwell c |
| - |
| 36.0 rockwell c and 40.0 rockwell c |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon flats |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon flats Material: |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Material Specification: |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Mil-s-5000 cond c2 military specification single material response |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Mil-s-5000 cond c2 military specification single material response Surface Treatment: |
| 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Mil-s-5000 cond c2 military specification single material response Surface Treatment: Cadmium and chromate |

N/a

NSN 5306-00-881-3220

Machine Bolt - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

