## NSN 5306-00-881-4595

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-881-4595 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.624 inches **Fastener Length:** Between 0.302 inches and 1.322 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.040 inches and 0.050 inches **Extended Washer Thickness:** 0.120 inches **Hole Diameter:** Between 0.042 inches and 0.050 inches **First Diameter From Head:** Between 0.161 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.158 inches and 0.178 inches **Thread Diameter:** 0.190 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Double hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 

**Product Name:** 

Navy special project

## NSN 5306-00-881-4595

Externally Relieved Body Bolt - Page 2 of 2



Material:
Steel comp 431
Material Specification:
Ams 5628 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0