

View Online at <https://aerobasegroup.com/nsn/5306-00-881-4596>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.615 inches and 0.695 inches

**Fastener Length:**

Between 1.240 inches and 1.260 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

0.120 inches

**Hole Diameter:**

0.046 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.565 inches and 0.625 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon longitudinal hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 431

**Material Specification:**

Ams 5628 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0