

View Online at <https://aerobasegroup.com/nsn/5306-00-883-3815>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.555 inches

Fastener Length:

0.930 inches

Head Style:

Double hexagon extended washer

Head Height:

0.388 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

0.091 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Single Shear Strength:

14300 pounds per square inch

Thread Diameter:

0.375 inches

Grip Length:

0.375 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hole Configuration Style:

Double hexagon flats

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.