

View Online at <https://aerobasegroup.com/nsn/5306-00-886-1431>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.390 inches and 0.430 inches

Fastener Length:

Between 3.740 inches and 3.760 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 0.990 inches and 1.010 inches

Head Height:

Between 0.230 inches and 0.270 inches

Width Between Flats:

Between 0.860 inches and 0.880 inches

Shank Unthreaded Hole Diameter:

0.143 inches first hole and 0.149 inches first hole

Thread Diameter:

0.562 inches

Grip Length:

Between 3.320 inches and 3.360 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

240000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.570 inches first hole and 3.590 inches first hole

Surface Finish:

50.0 microinches head

Material:

Steel

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-26074 spec.