

View Online at <https://aerobasegroup.com/nsn/5306-00-886-1431>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.390 inches and 0.430 inches

**Fastener Length:**

Between 3.740 inches and 3.760 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

Between 0.990 inches and 1.010 inches

**Head Height:**

Between 0.230 inches and 0.270 inches

**Width Between Flats:**

Between 0.860 inches and 0.880 inches

**Shank Unthreaded Hole Diameter:**

0.143 inches first hole and 0.149 inches first hole

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 3.320 inches and 3.360 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

240000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.570 inches first hole and 3.590 inches first hole

**Surface Finish:**

50.0 microinches head

**Material:**

Steel

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Mil-c-26074 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-26074 spec.